

## **MOUSSOL®-APS LV Premium 1/3 F-15 #6471**

ALCOHOL RESISTANT AFFF FOAM CONCENTRATE



### **Description**

MOUSSOL®-APS LV Premium 1/3 F-15 is an alcohol resistant low viscosity AFFF fire extinguishing foam concentrate without added polysaccharides. It is based on special, fluorinated components, surfactants, antifreezing compounds and foam stabilisers.

MOUSSOL®-APS LV Premium 1/3 F-15 is a newtonian liquid and does not contain polymers. In parts, the product is made from natural, renewable sources. The fluorinated components contained in MOUSSOL®-APS LV Premium 1/3 F-15 are in full compliance with Directive EU 757/2010.

### **Properties**

Due to its low viscosity, MOUSSOL®-APS LV Premium 1/3 F-15 flows freely up to the freeze point. The foam is resistant against polar solvents and non-polar, foam destroying hydrocarbons alike. On non-polar hydrocarbons MOUSSOL®-APS LV Premium 1/3 F-15 forms an extremely thin, aqueous film which flows ahead of the foam. A relatively short water drainage time enhances aqueous film formation and the flowability of the foam. This effect reduces the extinction time significantly and cools down the fire source. Aqueous film forming components allow its non-aspirated application on mineral oil based hydrocarbons. On polar solvents, a film forms which provides for a safe barrier against the foam destroying properties of the chemical.

MOUSSOL®-APS LV Premium 1/3 F-15 provides for fast and effective extinction of class A + B fires. The foam is stable and forms a lasting, gastight layer over the flammable surface. The risk of re-ignition of extinguished areas is reduced considerably.

### **Application**

MOUSSOL®-APS LV Premium 1/3 F-15 is used with all standard low expansion foam installations and mobile equipment. It is specially designed for polar, foam destroying liquids, e.g. alcohols, esters, ketones as well as non-polar hydrocarbons, e.g. petroleum products. The induction rate is 3% in water for polar solvents and 1% for hydrocarbon fires. Aqueous film forming fluorine components allow for non-aspirated application on non-polar hydrocarbons.

MOUSSOL®-APS LV Premium 1/3 F-15 is also used to cover spilled chemicals to prevent flammable and toxic gas emissions. A gentle foam application is required in order to combat polar solvent fires effec-

tively (see technical leaflet TM 037 „Extinguishing alcohol fires“).

MOUSSOL®-APS LV Premium 1/3 F-15 is used with tap water, seawater, brackish water and treated industrial water. When used in the presence of electrical installations observe DIN/VDE-0132, or equivalent national standards.

### **Environment**

None of the raw materials used in our products are banned. Our foam concentrates comply with the latest environmental regulations, such as 'Commission Regulation (EU) No 757/2010', amending '(EC) No 850/2004.' MOUSSOL®-APS LV Premium 1/3 F-15 will also comply with the 'significant new use rule (SNUR)' for long-chain perfluoroalkyl carboxylate proposed by the Environmental Protection Agency, which will come into effect in due course.

### **Compatibility with other foam concentrates**

#### Mixing for immediate use:

MOUSSOL®-APS LV Premium 1/3 F-15 can be mixed at any proportion with equivalent foam concentrates if used immediately.

#### Mixing for long term storage:

It is not recommended to mix MOUSSOL®-APS LV Premium 1/3 F-15 with equivalent foam concentrates when stored. Prior to replenishment, the quality of MOUSSOL®-APS LV Premium 1/3 F-15 stocks should be examined by our laboratory.

#### Mixing with synthetic concentrates:

MOUSSOL®-APS LV Premium 1/3 F-15 must not be mixed with other types foam concentrates.

#### Mixing with other expanded foams:

MOUSSOL®-APS LV Premium 1/3 F-15 foam is compatible with all other generated fire fighting foams.

### **Compatibility with powder**

MOUSSOL®-APS LV Premium 1/3 F-15 is suitable for the combined use with foam compatible dry chemical powders.

### **Packaging**

MOUSSOL®-APS LV Premium 1/3 F-15 is available in plastic cans, plastic drums, IBC's (totes) and in bulk.

# MOUSSOL®-APS LV Premium 1/3 F-15 #6471

## ALCOHOL RESISTANT AFFF FOAM CONCENTRATE



### Storage

MOUSSOL®-APS LV Premium 1/3 F-15 is stored long term in the sealed original containers or in non-corrosive plastic or stainless steel tanks. High temperatures up to 50°C do not affect the quality, neither does temporary freezing below the specified frost resistance limit (see technical leaflet TM 014 "Storage of synthetic foam concentrates"). Before re-filling foam concentrate stocks arrange for a quality check-up by our laboratory.

### Shelf Life

MOUSSOL®-APS LV Premium 1/3 F-15 has a shelf life of >10 years, if stored according to our recommendations (see technical info leaflet TM014 'Storage of Synthetic Fire Extinguishing Foam Concentrates').

### Conformity/Listings

MOUSSOL®-APS LV Premium 1/3 F-15 is approved as fire extinguishing agent for fires of class A and B according to the following standards:



EN 1568:2008 - Certificate No.: KB-268/14  
Part 3 (Heptane): IA/IA  
Part 4 (Aceton): IC/IC --- (IPA): IB/IC



ICAO Airport Services Manual  
Low expansion foam --- Level B



IMO MSC.1/Circ. 1312 non-polar (Heptane)  
IMO MSC.1/Circ. 1312 polar (Alcohol)



LASTfire  
good --- good --- good

Physical properties and technical data		MOUSSOL®-APS LV Premium 1/3 F-15	
Recommended induction rate	1% 3%	low expansion foam low expansion foam	non-polar liquids polar liquids
Foam expansion* (according to EN 1568)	6 - 10	low expansion foam*	
25%/50% water drainage time* (according to EN 1568)	1 - 5 minutes	3 - 7 minutes	low expansion foam*
Colour	yellow to brown		
pH value	at 20°C	6,5 - 8,5	
Density	at 20°C	1,060 ± 0,02 g/ml	
Sediments	none		
Surface tension/Spreading coefficient	< 17,5 mN/m	> 3 mN/m (Cyclohexane)	
Frost resistance	-15°C		
Viscosity	at 20°C at 0°C at -15°C	< 15 < 25 < 50	mm²/sec mm²/sec mm²/sec
Environmental acceptability	MOUSSOL®-APS LV Premium 1/3 F-15 is readily bio degradable. Fluorine components are not fully degradable. See material safety data sheet for further information.		
Special notes	MOUSSOL®-APS LV Premium 1/3 F-15 poses no health risk, provided it is used as intended as fire extinguishing foam. Firefighting exercise and testing may have to be agreed with local authorities. Consider when spraying persons with foam that they will not be able to breathe whilst covered with foam. See material safety data sheet for further information.		



# Dr. STHAMER HAMBURG

Hauptsitz Hamburg:  
Liebigstraße 5 • 22113 Hamburg/Germany  
Tel.: +49 (0)40 736168-0 • Fax: +49 (0)40 736168-0  
info@sthamer.com • www.sthamer.com

Verkaufsbüro Hannover:  
Tel.: +49 (0)511 76835845  
Fax: +49 (0)511 76835846

Verkaufsbüro Jena:  
Tel.: +49 (0)3641 6353857  
Fax: +49 (0)3641 6353859

