



vaPUREx® FXS AR 3/3 F-0 #2365



ALCOHOL RESISTANT FOAM CONCENTRATE

vaPUREx® FXS AR 3/3 F-0 is a highly effective, universal firefighting foam agent for use in critical risk areas where polar^{*1} flammable liquids (e.g. alcohols, ketones, organic acids, etc.), non-polar^{*2} hydrocarbons (diesel, kerosene, gasoline, crude oil, etc.) respectively other chemicals are produced, processed, decanted, transported or stored.

The good foamability, a very free-flowing and well-sealing, unusually stable low expansion foam and its maximum robustness against changing operating conditions (fluctuations in the admixture, water quality, fuel influence, etc.) are the outstanding features of this exceptionally efficient product.

The firefighting foam agent meets the highest standards of environmental compatibility and is therefore available to the user for all application scenarios.

Performance

vaPUREx® FXS AR 3/3 F-0 is readily biodegradable and free of organic fluorine compounds^{*3} and preservatives. The particularly good environmental profile of vaPUREx® FXS AR 3/3 F-0 is proven by its classification in water hazard class (WGK) 1, or the classification of the concentrate with one point according to the Bavarian environmental classification model^{*4}.

vaPUREx® FXS AR 3/3 F-0 foam has an exceptional high water-holding capacity and special viscoelastic properties that significantly determine its performance profile: the foam becomes very free-flowing, seals well and is particularly stable against heat and air movement. Smaller destructions of the foam blanket (e.g. by falling objects) will automatically heal which guarantees high securing capabilities.

vaPUREx® FXS AR 3/3 F-0 is resistant to non-polar^{*2} as well as to foam-destroying, polar^{*1} hydrocarbons and mixtures thereof. A stable polymer film forms on polar^{*1}, foam-destroying liquid hydrocarbons, protecting the foam blanket from further destruction.


vaPUREx® FXS AR 3/3 F-0 proves to be exceptionally application robust: extensive tests with varying admixture, on different liquid fuels and different foam qualities confirm the outstandingly high application reliability.

Technical Specification

Appearance	colourless/yellow
Fire Class/-es	A + B
Lowest Use Temperature	Protect from Freezing
Max. Storage Temperature	max. +50 [°C]
Specific Gravity (20°C)	1,030 ± 0,02 [g/ml]
pH value (20°C)	6,5 - 8,5
Viscosity (20°C)	< 570(190) [mPa*s bei 75(375) 1/s]
Sedimentation	Sediment Free

Foam Properties acc. to EN1568 at 20°C

Induction Rate	3%
Expansion Rate	7 - 11, 60 - 100
25% Drainage Time	> 30, > 17 [min]
50% Drainage Time	> 60, > 20 [min]
Expansion Types	Low -, Medium Expansion Foam



*as mentioned in the respective test standard or in the text

Performance Tests

DIN EN 1568	EN 1568:2018 - Approval-No.: KB250/22 Part 3 (Heptane): IA/- Part 4 (Acetone): IA/- --- (IPA): IA/- Part 1: Medium Expansion Foam
ICAO	ICAO Airport Services Manual Low Expansion Foam --- Level B
VdS	VdS Approval: non-expanded application through foam sprinklers on polar and non-polar liquids
FM	FM 5130 Approval also see FM Approval Guide (www.ApprovalGuide.com)

Application

The main areas of application are the chemical and mineral oil industries, the aviation sector (airports, helicopter decks) and the maritime on- and offshore sector (ports, platforms, shipping).

vaPUREx® FXS AR 3/3 F-0 is suitable for all qualities of water (fresh water, industrial water free of foam-destroying additives, sea water and brackish water). The proportioning rate to fire water is 3% for all applications.

Due to increased viscosity and pseudoplastic property, pump assisted admixing is recommended at concentrate temperatures < 5°C. Since the viscosity of a foam extinguishing concentrate also depends on its temperature, it is recommended to test the delivery and proportioning equipment at least once at the temperature limits to be expected typical for the use scenario. Please contact us for suitable equipment or appropriate testing.

vaPUREx® FXS AR 3/3 F-0 can be expanded to give low - and medium expansion foam with any commercially available foam generating devices and is suitable to fight fires of the fire classes A and B (polar and non-polar). Low expansion foam made from vaPUREx® FXS AR 3/3 F-0 can be applied directly onto fires of non-polar² liquids (indirect foam application is usually more efficient and preferable). Foam should be applied gently⁵ to fires of polar liquids to achieve optimum extinguishing success (see technical leaflet TM 037 "Extinguishing alcohol fires").

Due to its stable structure, the foam can also be applied to pools of flammable liquids for vapor suppression or as a preventive fire protection measure. vaPUREx® FXS AR 3/3 F-0 can be supplied as standard in 1,000 litre PE IBCs.

Medium expansion foam produced from solutions of vaPUREx® FXS AR 3/3 F-0 has a homogeneous bubble structure, flows well and is stable.

Compatibility

When mixing different firefighting foam agents, it must be considered that the resulting mixture is a new chemical product which is not tested as firefighting foam agent and also must be re-evaluated and labelled according to hazardous materials regulations.

vaPUREx® FXS AR 3/3 F-0 shall under no circumstances be mixed with other firefighting foam concentrates or -solutions, neither as a concentrate nor as a premix. Even the smallest quantities can render the products concerned non-useable, respectively lead to precipitation or agglomeration and consequently to equipment failure.

The foam produced from vaPUREx® FXS AR 3/3 F-0 is fully compatible with all other ready expanded firefighting foams.

Storage & Shelf Life

When synthetic firefighting foam agents and concentrates are stored, only certain materials in only certain combinations are suitable for permanent media contact. Our detailed Technical Information Nos. 014 (Storage of synthetic firefighting foam concentrates) and 009 (Material suitability polymers) provide information on this and other important aspects for the optimum storage of our products. Please do not hesitate to contact us for further information. On short-term contact and subsequent thorough cleaning with water, vaPUREx® FXS AR 3/3 F-0 or a premix solution made from it will not corrode metals such as copper, aluminium, brass, admiralty brass or bronze.

⁵ e.g. via pouring elbows, foam baffles, or roll-on or rain-down technique

Elevated temperatures up to a maximum of +50°C or temporary freezing at temperatures below the specified frost resistance limit do not affect this high-quality product adversely (see our further Technical Information on the storage of firefighting foam agents). Temperature should not exceed +50°C.

Before filling storage tanks, these tanks and all supply lines, pumps, valves or other parts carrying media must be thoroughly cleaned, free of grease and free of residues from a previous filling. Before filling up stocks of our vaPUREx® FXS AR 3/3 F-0 we recommend to have a quality test of the stock to be filled up carried out in our laboratory. If stored according to our storage recommendations, a shelf life of well over ten years is possible.

Environment

vaPUREx® FXS AR 3/3 F-0 was fully toxicologically tested. The product is readily biodegradable.

Unused product (concentrate) must not be released into the environment. Disposal must be carried out in consultation with local authorities and specialised waste treatment companies.

Please also note further information in our safety data sheet!

Transport

vaPUREx® FXS AR 3/3 F-0 is available in the following packaging units: PE-canister (20 ltr, 25 ltr and 60 ltr), PE-canister according to DIN 14452 (20 ltr); PE-drum (200 ltr), PE-IBC (600 ltr und 1.000 ltr) or bulk.

Please contact us for special packing sizes.



For further Documentation please scan the Qr code or see <http://sthamer.de/qr/2365>



Safety Advice: Please bear in mind that foam solutions are electroconductive liquids. The use in proximity to electrical/electronic equipment can require specific safety measures.



Safety Advice: Please see our Technical Information regarding "Mixing of Foam Concentrates" for further information

Disclaimer:

Disclaimer: Any information in this product data sheet bases upon our best knowledge and expertise at the time of this issue. We reserve the right to change the content of this document or adapt to newer information. Please ask for the most recent revision of this data sheet.

Hauptsitz Hamburg Liebigstr. 5 22113 Hamburg Deutschland Tel.: +49 (0)40 73 61 68-0 Fax: +49 (0)40 73 61 68-60	Verkaufsbüro Hannover Hartenbrakenstr. 54 30659 Hannover Deutschland Tel.: +49 (0)511 768 358-45 Fax: +49 (0)511 768 358-46	Verkaufsbüro Jena Carl-Pulfrich-Str. 1 07745 Jena Deutschland Tel.: +49 (0)3641 63538-57 Fax: +49 (0)3641 63538-59	Büro Frankenthal Siemensstr. 4 67227 Frankenthal Deutschland Tel.: +49 (0)6233 3796-605 Fax: +49 (0)6233 3796-622	info@sthamer.com www.sthamer.com	
--	---	--	---	---	--